

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) EP 0 905 686 A2

(12) EUROPEAN PATENT APPLICATION

(43) Date of publication:
31.03.1999 Bulletin 1999/13

(51) Int. Cl.⁶: G11B 15/68, G11B 17/22

(21) Application number: 98118059.9

(22) Date of filing: 23.09.1998

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(30) Priority: 24.09.1997 JP 259046/97

(71) Applicant:
Victor Company of Japan, Ltd.
Yokohama 221-0022 (JP)

(72) Inventors:
• Yamanaka, Akira
Yokohama (JP)
• Shibuya, Naoki
Takasaki-chi, Gunma-ken (JP)

• Yomogida, Yasukazu
Sagamihara-shi, Kanagawa-ken (JP)
• Nishikawa, Kouichiro
Sagamihara-shi, Kanagawa-ken (JP)
• Adachi, Kengo
Sagamihara-shi, Kanagawa-ken (JP)
• Shintani, Isao
Maebashi-shi, Gumma-ken (JP)

(74) Representative:
Pellmann, Hans-Bernd, Dipl.-Ing. et al
Patentanwaltsbüro
Tiedtke-Bühling-Kinne & Partner
Bavariaring 4
80336 München (DE)

(54) Improved structure of stocker apparatus for storage medium

(57) A stocker apparatus for storage mediums such as minidisk cartridges is provided which includes a stocker tray moving mechanism designed to move stocker trays between a neutral and a storage medium loading/unloading position together. In the neutral position, the stocker tray moving mechanism lays the stocker trays (16, 17, 18) to overlap each other with storage medium loading/unloading openings being aligned vertically. In the storage medium loading/unloading position, the stocker tray moving mechanism shifts the stocker trays laterally by different distances so as to orient the storage medium loading/unloading openings diagonally upward for facilitating ease of manual loading and unloading of each storage medium into and from corresponding one of the stocker trays.




FIG. 1

EP 0 905 686 A2

AL-PA000010
CITED BY APPLICANT

Description

BACKGROUND OF THE INVENTION

1 Technical Field of the Invention

[0001] The present invention relates generally to a stocker apparatus designed to stock a plurality of storage mediums such as minidisk (minidisc, MD) cartridges, compact disks (compact discs, CDs), digital video disks (digital video discs, DVDs), or tape cassettes. 2 Background of Related Art

[0002] Japanese Patent First Publication No. 7-176126 teaches a conventional minidisk exchanging device with a cartridge transport mechanism which has a plurality of cartridge holders disposed to overlap each other and transports selected one of minidisk cartridges stocked in the cartridge holders to a playback station. When each minidisk cartridge is ejected from one of the cartridge holders, an eject button installed on a front panel is pushed to project the minidisk cartridge partially from the front panel, allowing the user to grasp the minidisk cartridge for withdrawal. The amounts of projection of the minidisk cartridges from the front panel are the same. The minidisk cartridges are laid to overlap each other with small intervals. It is, thus, easy to project only one of the minidisk cartridges from the front panel to withdraw it manually, but it is difficult to withdraw some of the minidisk cartridges simultaneously projected from the front panel.

[0003] Such a minidisk exchanging device is usually equipped with a loading error detecting mechanism designed to detect loading errors of minidisk cartridges independently. When a plurality of minidisk cartridges are loaded into cartridge holders simultaneously, the independent detection of a loading error of each minidisk cartridge is not always needed. It is advisable to detect loading errors of some or all of the minidisk cartridges together.

SUMMARY OF THE INVENTION

[0004] It is therefore a principal object of the present invention to avoid the disadvantages of the prior art.

[0005] It is another object of the present invention to provide an improved structure of a storage medium stocker apparatus which provides for ease of loading and unloading of storage mediums into and from the stocker apparatus.

[0006] It is a further object of the invention to provide an improved structure of a storage medium stocker apparatus designed to detect errors in loading storage mediums into the stocker apparatus.

[0007] According to one aspect of the present invention, there is provided a stocker apparatus for storage mediums which comprises a plurality of stocker trays for stocking therein storage mediums, respectively, and a stocker tray moving mechanism. Each of the stocker

tray has a storage medium loading/unloading opening. The stocker tray moving mechanism is designed to move the stocker trays between a first and a second position together. In the first position, the stocker tray moving mechanism lays the stocker trays so as to overlap each other with the storage medium loading/unloading openings being aligned substantially perpendicular to a reference plane. In the second position, the stocker tray moving mechanism shifts the stocker trays laterally by different distances so as to orient the storage medium loading/unloading openings upward in alignment with a diagonal line extending at a given angle to the reference plane for loading and unloading the storage mediums into and from the stocker trays.

[0008] In the preferred mode of the invention, the stocker tray moving mechanism includes a chassis, a base frame, a sub-frame, a cam groove, and a cam plate. The base frame is installed on the chassis so as to be movable substantially parallel to the reference plane. The sub-frame is mounted pivotably on the base frame and retains the stocker trays to overlap each other vertically. The cam groove is formed in the chassis along which a cam follower connecting with the sub-frame moves to swing the sub-frame relative to the base frame according to movement of the base frame substantially parallel to the reference plane. The cam plate is supported pivotably by a pivot installed on the base frame and thrusts the stocker trays laterally from the sub-frame by the different distances which are determined as a function of intervals between the pivot on the base frame and the stocker trays.

[0009] A door is further provided which opens and closes a storage medium loading/unloading openings of the chassis selectively according to the movement of the base frame.

[0010] According to another aspect of the invention, there is provided a stocker apparatus for storage mediums which comprises a plurality of stockers and a shutter. The stockers are laid to overlap each other in a direction substantially perpendicular to a loading/unloading direction in which cartridges holding therein storage mediums are loaded into and unloaded from the stockers. Each of the stockers is designed to receive the cartridge inside a reference line when the cartridge is loaded at a correct orientation and to project an end portion of the cartridge from the reference line when the cartridge is loaded at an incorrect orientation. The shutter is movable between a first and a second position in a direction substantially perpendicular to the loading/unloading direction of the cartridges. In the first position, the shutter lies at a given interval away from the cartridges without interfering with loading and unloading of the cartridges into and from the stockers. In the second position, the shutter covers the end portions of the cartridges at least partially when all the cartridges are loaded into the stockers at the correct orientation and collides with the end portion of at least one of the cartridges projecting from the reference line

when the at least one of the cartridge is loaded into corresponding one of the stockers at the incorrect orientation.

[0011] According to a further aspect of the invention, there is provided a stocker apparatus for storage medium which comprises a stocker mechanism and a shutter. The stocker mechanism has a stocker frame retaining a plurality of stocker trays for stocking therein cartridges which hold storage mediums and moves the stocker trays between a first and a second position together. In the first position, the stocker trays are laid to overlap each other with storage medium loading/unloading openings being aligned substantially perpendicular to a reference plane. In the second position, the stocker trays are shifted laterally relative to the stocker frame for facilitating ease of loading and unloading of each of the cartridges into and from corresponding one of the stocker trays. Each of the stocker trays is designed to receive the cartridge inside a reference line when the cartridge is loaded at a correct orientation and to project an end portion of the cartridge from the reference line when the cartridge is loaded at an incorrect orientation. The shutter is movable between a first and a second shutter position in a direction substantially perpendicular to the loading/unloading direction of the cartridges. In the first shutter position, the shutter lies at a given interval away from the cartridges without interfering with loading and unloading of the cartridges into and from the stocker trays. In the second shutter position, the shutter covers the end portions of the cartridges at least partially when all the cartridges are loaded into the stocker trays at the correct orientation and collides with the end portion of at least one of the cartridges projecting from the reference line when the at least cartridge is loaded into corresponding one of the stocker trays at the incorrect orientation.

[0012] In the preferred mode of the invention, the stocker mechanism includes a cam mechanism which moves the stocker trays and the shutter.

[0013] The shutter covers the end surfaces of the cartridges at least partially when all the cartridges are loaded into the stocker trays at the correct orientation for avoiding additional loading of cartridges.

BRIEF DESCRIPTION OF THE DRAWINGS

[0014] The present invention will be understood more fully from the detailed description given hereinbelow and from the accompanying drawings of the preferred embodiment of the invention, which, however, should not be taken to limit the invention to the specific embodiment but are for explanation and understanding only.

[0015] In the drawings:

Fig. 1 is a perspective view which shows a storage medium stocker according to the present invention; Fig. 2 is an exploded view which shows the storage medium stocker in Fig. 1;

Fig. 3(a) is an exploded view which shows a stocker tray;

Fig. 3(b) is a partially perspective view which shows two stocker trays disposed below the one shown in Fig. 3(a);

Fig. 4 is a plan view which shows a stocker tray;

Fig. 5 is a side view which shows a door unit;

Fig. 6 is an exploded view which shows a loading error detecting mechanism;

Fig. 7 is a plan view which shows a drive mechanism actuating stocker trays and a shutter;

Fig. 8 is a plan view which shows an neutral position of the drive mechanism of Fig. 7;

Fig. 9 is a plan view which shows a position of a drive mechanism following the initial position in Fig. 8;

Fig. 10 is a plan view which shows a position of a drive mechanism following the position in Fig. 9;

Fig. 11 is a plan view which shows a position of a drive mechanism following the position in Fig. 10;

Fig. 12 is a plan view which shows a loading position of a stocker tray which allows an MD (minidisc) cartridge to be loaded into a minidisk reproduction device;

Fig. 13(a) is a side view which shows an initial position of a stocker mechanism;

Fig. 13(b) is a side view of the stocker mechanism of Fig. 13(a) from which a right side chassis is omitted;

Fig. 14(a) is a side view which shows a position of a stocker mechanism following the initial position in Fig. 13(a);

Fig. 14(b) is a side view of the stocker mechanism of Fig. 14(a) from which a right side chassis is omitted;

Fig. 15(a) is a side view which shows a position of a stocker mechanism following the position in Fig. 14(a);

Fig. 15(b) is a side view of the stocker mechanism of Fig. 15(a) from which a right side chassis is omitted;

Fig. 16(a) is a side view which shows the frontmost position of a stocker mechanism wherein a base frame reaches a cartridge loading/unloading position which allows MD cartridges to be loaded into or unloaded from stocker trays;

Fig. 16(b) is a side view of the stocker mechanism of Fig. 16(a) from which a right side chassis is omitted;

Fig. 17(a) is a side view which shows the rearmost position of a stocker mechanism wherein a base frame reaches a loading position which allows MD cartridges to be withdrawn from stocker trays into a minidisk reproduction device;

Fig. 17(b) is a side view of the stocker mechanism of Fig. 17(a) from which a right side chassis is omitted;

Figs. 18(a) and 18(b) are plan views which show a

stocker tray into which an MD cartridge is loaded at a correct orientation;

Figs. 19(a) and 19(b) are plan views which show a stocker tray into which an MD cartridge is loaded at incorrect orientations;

Fig. 20 is a plan view which shows the state of a loading error detecting mechanism when an MD cartridge is being loaded at a correct orientation into a stocker tray in a cartridge loading/unloading position;

Fig. 21(a) is a plan view which shows the state of a loading error detecting mechanism when an MD cartridge reaches a standby position after loaded into a stocker tray;

Fig. 21(b) is a partially perspective view of the loading error detecting mechanism of Fig. 21(a);

Fig. 22 is a plan view which shows the state of a loading error detecting mechanism when an MD cartridge is turned 90° counterclockwise in error and loaded into a stocker tray;

Fig. 23(a) is a plan view which shows the state of a loading error detecting mechanism when an MD cartridge reaches a standby position after loaded into the stocker tray at the incorrect orientation in Fig. 22; and

Fig. 23(b) is a partially perspective view of the loading error detecting mechanism in Fig. 23(a).

DESCRIPTION OF THE PREFERRED EMBODIMENT

[0016] Referring now to the drawings, particularly to Fig. 1, there is shown a storage medium stocker 1 according to the invention which is mounted on, for example, the front of the minidisk reproduction device 100 as represented by a two-dot chain line.

[0017] The storage medium stocker 1 includes generally the stocker mechanism 10, the door unit 40, the loading error detecting mechanism 50, and the drive mechanism 60. The stocker mechanism 10 is designed to hold a plurality of minidisk (MD) cartridges 150 so as to be overlaid with each other. The door unit 40 covers the front of the stocker mechanism 10. The loading error detecting mechanism 50 is installed in front of the stocker mechanism 10 to detect a failure in loading of each MD cartridge 150. The drive mechanism 60 is designed to move the base frame 12 back and forth relative to the chassis 11 of the stocker mechanism 10 and to move the shutter 51 of the loading error detecting mechanism 50 laterally.

[0018] In operation, as will be discussed later in detail, one of the MD cartridges 150 held in first to third stocker trays 16 to 18 of the storage medium stocker 1 is selectively loaded into the minidisk reproduction device 100 to record or read information signals on and out of it. The minidisk reproduction device 100 is so designed that a loader can be moved up and down to pick up the selected one of the MD cartridges 150 from corresponding one of the first to third stocker trays 16 to 18.

[0019] The stocker mechanism 10, as clearly shown in Fig. 2, includes the chassis 11, the base frame 12, sub-frame 13, the partition cover 14, the cam plates 15, and the first to third stocker trays 16 to 18. The chassis 11 consists of side chassis 22 and 23 extending in parallel and the upper chassis 21 disposed over the side chassis 22 and 23. The base frame 12 is disposed in the chassis 11 so as to be slidable in a loading direction of the MD cartridges 150. The sub-frame 13 is retained pivotably by the base frame 12. The partition cover 14 is installed on the sub-frame 13 to cover a front open end thereof. The cam plates 15 are mounted on right and left outer side walls of the base frame 12 (only one is shown for the brevity of illustration). The first to third stocker trays 16 to 18 are retained by the right and left side walls of the sub-frame 13 so as to overlap each other vertically. Specifically, the first stocker tray 16 is fixed near the upper wall of the sub-frame 13, while the second and third stocker trays 17 and 18 are disposed slidably in parallel to the first stocker tray 16.

[0020] The chassis 11, as described above, consists of the side chassis 22 and 23 and the upper chassis 21. The upper chassis 21 has mounted thereon pins 21a and 21b for installation of the loading error detecting mechanism 50 as shown in Fig. 1 and also has formed therein grooves 21c, 21d, and 21e for guiding lateral movement of the drive plate 52 which actuates the loading error detecting mechanism 50 and grooves 21f and 21g along which pins 12b and 12c installed on the upper wall of the base frame 12 slide to move the base frame 12 longitudinally.

[0021] The upper chassis 21 has, as clearly shown in Figs. 1 and 7, also mounted on the back surface thereof a set of gears 61a, 62, 63, and 64 which make up the drive mechanism 60 as will be described later in detail.

[0022] The side chassis 22 has formed therein the grooves 22a and 22b extending in alignment with each other and the cam groove 22c. The grooves 22a and 22b guide longitudinal movement of the pins 12d and 12e installed on the side wall of the base frame 12. The cam groove 22c controls movement of the pin 25b installed on a rear end portion of the side plate 25 of the sub-frame 13 for swinging the sub-frame 13, as will be discussed later in detail.

[0023] The side chassis 23 is the mirror image of the chassis 22. Specifically, the side chassis 23 has formed therein grooves 23a and 23b for sliding the base frame 12 and the cam groove 23c for swinging the sub-frame 13.

[0024] The base frame 12 has the pinion 64 secured on the upper surface, a pair of pins 12b and 12c mounted on the upper surface longitudinally, a pair of pins 12d and 12e mounted on the right side surface, a pair of pins 12f and 12g mounted on the left side surface, a pair of holes 12h (only one is shown) formed in the both side surfaces, and a pair of pins or pivots 12i (only one is shown) mounted on the both side surfaces. The rack 63 extends longitudinally, i.e., parallel to the

center line J-J and meshes with the pinion 64 of the drive mechanism 60 disposed on the reverse surface of the upper chassis 21 to move the base frame 12 longitudinally. The pins 12b and 12c engage the grooves 21f and 21g formed in the upper chassis 21. The pin 12b engages a cam groove formed in the plate 52 of the loading error detecting mechanism 50 as will be described later in detail. The pins 12d and 12e engage the grooves 22a and 22b formed in the right side chassis 22. Similarly, the pins 12f and 12g engage the grooves 23a and 23b formed in the left side chassis 23. The holes 12h receive the pivots 25a (only one is shown) mounted on front portions of side surfaces of the sub-frame 13 to allow the sub-frame 13 to rotate about the pivots 25a. The pivots 12i supports the cam plates 15 rotatably.

[0025] The sub-frame 13 consists of the upper plate 24 and right and left side plates 25 and 26 extending downward from both sides of the upper plate 24.

[0026] The side plate 25 has the pivot 25a engaging the hole 12h of the base frame 12, the pin 25b for allowing the swing of the cam plate 15, a pair of circular holes 25c for securing the first stocker tray 16 rigidly, a pair of elongated holes 25d for guiding sliding movement of the second stocker tray 17, and a pair of elongated holes 25e for guiding sliding movement of the third stocker tray 18.

[0027] The side plates 26 is the mirror image of the side plate 25, and explanation thereof in detail will be omitted here.

[0028] The partition cover 14 is, as described above, attached to the front of the sub-frame 13 and has first, second, and third loading openings 14a, 14b, and 14c formed parallel to each other for loading the MD cartridges 150 into the first, second, and third stocker trays 16, 17, and 18, respectively.

[0029] The cam plate 15 mounted on the right side wall of the base frame 12 has the hole 15a into which the pivot 12i of the base frame 12 is inserted, the horizontally elongated hole 15b into which the pin 25b of the right side plate 25 of the sub-frame 13 is inserted, and a pair of vertically elongated holes 15c and 15d for guiding longitudinal movement of the second and third stocker trays 17 and 18, respectively. The cam plate 15 mounted on the left side wall of the base frame 12 has a similar structure, and explanation thereof in detail will be omitted here.

[0030] The base frame 12, the sub-frame 13, the partition cover 14, and the first to third stocker trays 16 to 18 are, as will be discussed later in detail, moved within the chassis 11 from a standby position to a front cartridge loading/unloading position and a rear loading position.

[0031] The first stocker tray 16, as clearly shown in Fig. 3(a), consists of the tray body 31, right and left lock levers 32 and 33 pivotably mounted on upper surfaces of side walls extending vertically from both sides of the tray body 31, the slide plate 34 slidably mounted on the reverse surface of the tray body 31 in connection with

the lock levers 32 and 33, the tension spring 35 stretched between the slide plate 34 and the tray body 31, the pressure bar (leaf) spring 36 producing the pressure to hold the MD cartridge 150 within the tray body 31 (see Fig. 1), and the release lever 37 mounted on a rear portion of the reverse surface of the tray body 31 in connection with the slide plate 34.

[0032] The tray body 31 has guide surfaces 31a and 31b formed on the side walls thereof for guiding movement of both sides of the MD cartridge 150, the upper guide surface 31c continuing from the guide surface 31a, upper guide surfaces 31d and 31e continuing from the guide surface 31b, and two pairs of pins 31f installed on outer surfaces of the side walls, inserted into the circular holes 25c of the side plates 25 and 26 of the sub-frame 13, respectively.

[0033] The width of the tray body 31 (i.e., the distance between the guide surfaces 31a and 31b) is so determined as to allow smooth insertion of the MD cartridge whose width W, as shown in Fig. 18(a), is 71.4 mm without any play. Specifically, the guide surfaces 31a and 31b of the tray body 31 serve to orient loading and unloading movement of the MD cartridge 150 along a predetermined loading/unloading direction.

[0034] The depth D (= 68 mm), as shown in Fig. 18(a), of the MD cartridge 150 is slightly shorter than the width W (= 71.4 mm). Therefore, if the MD cartridge 150 is loaded in error with the front and the back thereof facing the guide surfaces 31a and 31b, it will cause the play to be developed between the MD cartridge 150 and the guide surfaces 31a and 31b. This loading error is, as discussed later in detail, detected by the loading error detecting mechanism 50.

[0035] The right lock lever 32 has the hole 32a for attachment to the tray body 31, the hook 32b locking the MD cartridge 150, and a pin or cam follower 32c inserted into the cam groove 34b formed in the slide plate 34.

[0036] Similarly, the left lock lever 33 has the hole 33a for attachment to the tray body 31, the hook 33b locking the MD cartridge 150, and a pin or cam follower 33c inserted into the cam groove 34c formed in the slide plate 34.

[0037] The lock levers 32 and 33 serve to hold the MD cartridge 150 in a preselected position in the first stocker tray 16.

[0038] The slide plate 34 has a pair of holes 34a elongated longitudinally in alignment with each other, the cam groove 34b for guiding movement of the right lock lever 32, and the cam groove 34c for guiding movement of the left lock lever 33, and the pin 34d connected to the release lever 37. The holes 34a engage protrusions (not shown) formed on the reverse surface of the tray body 31, respectively, for guiding longitudinal movement of the slide plate 34.

[0039] The release lever 37 has the hole 37a for pivotal attachment to the reverse surface of the tray body 31, the elongated hole 37b into which the pin 34d of the

slide plate 34 is inserted, and the extension 37c which is brought in operation into contact with the minidisk reproduction device 100.

[0040] The second and third stocker trays 17 and 18 have substantially the same structure as that of the first stocker tray 16 except that the pins 31g and 31h, as shown in Fig. 3(b), installed on the outer surfaces of the right side walls of the second and third stocker trays 17 and 18 are longer than the pins 31f of the first stocker tray 16. The front pins 31g engage the horizontally elongated holes 25d and 25e, as shown in Fig. 2, formed in the front portion of the right side plate 25 of the sub-frame 13. The rear pins 31h engage the horizontally elongated holes 25d and 25e formed in the rear portion of the side plate 25 and the vertically elongated holes 15c and 15d of the cam plate 15.

[0041] Each of the second and third stocker trays 17 and 18 also has installed on the left side thereof the same pins as the pins 31g and 31h as described above.

[0042] Fig. 4 is a plan view which illustrates the first stocker tray 16. In the drawing, the right lock lever 32 is rotatable clockwise about the hole 32a, the left lock lever 33 is rotatable counterclockwise about the hole 33a, the slide plate 34 is movable toward the minidisk reproduction device 100, and the release lever 37 is rotatable clockwise.

[0043] In operation, when the first stocker tray 16 holding the MD cartridge 150 is moved from the standby position to the loading position, as will be described later in detail, the extension 37c of the release lever 37 is brought into contact with the minidisk reproduction device 100, thereby causing the release lever 37 to be rotated clockwise, which rotation, in turn, causes the slide plate 34 connected to the release lever 37 to be moved toward the minidisk reproduction device 100. The movement of the slide plate 34 causes the right and left lock levers 32 and 33 to swing outward of the first stocker tray 16, so that the hooks 32b and 33b are moved out of engagement with the MD cartridge 150, thereby allowing the MD cartridge 150 to be loaded into the minidisk reproduction device 100.

[0044] The second and third stocker trays 17 and 18 operate in the same manner as described above, and explanation thereof in detail will be omitted here.

[0045] Fig. 5 shows the side of the door unit 40.

[0046] The door unit 40 includes the door 41 pivotally mounted on a front panel (not shown), the fan-shaped gear 43 pivotally mounted on the outer surface of the right chassis 22 for opening and closing the door 41, and the drive lever 46 connected to the gear 43 through the transmission lever 44 and the tension spring 45.

[0047] The door 41 consists of the door body 41a, the right and left pivots 41b (only one is shown) supported by the front panel, and a half-moon gear 41c meshing with the fan-shaped gear 43.

[0048] The fan-shaped gear 43 has the hole 43a for pivotal attachment to the outer surface of the right chassis 22, the gear 43b for meshing with the half-moon

gear 41c, the support 43c retaining an end of the tension spring 45, and the stopper 43d for controlling the movement of the transmission lever 44.

[0049] The transmission lever 44 has the hole 44a for pivotal attachment to the outer surface of the right chassis 22 through the fan-shaped gear 43, the pin 44b engaging the cam groove 46c of the drive lever 46, and the support 44c retaining the end of the tension spring 45.

[0050] The drive lever 46 has the hole 46a for pivotal attachment to the outer surface of the right chassis 22, the elongated hole 46b into which the pin 12e of the base frame 12 (see Fig. 2) is inserted, and the cam groove 46c into which the pin 44b of the transmission lever 44 is inserted.

[0051] In operation, when the pin 12e of the base frame 12 moves forward (i.e., the left in the drawing), it will cause the drive lever 46 to be rotated counterclockwise about the hole 46a, so that the pin 44b of the transmission lever 44 moves from a vertically extending portion to a horizontally extending portion of the cam groove 46c to swing the fan-shaped gear 43 about the hole 43a through the tension spring 45. The fan-shaped gear 43 meshes with the half-moon gear 41c to open the door 41 along with the forward movement of the first to third stocker trays 16 to 18, as clearly shown in Fig. 1. The tension spring 45 serves as a safety device when the door 41 is moved by a hand of a user. After the door 41 is opened fully, the fan-shaped gear 43 and the transmission lever 44 remain stopped while the pin 44b of the transmission lever 44 moves along the horizontally extending portion of the cam groove 46c.

[0052] Fig. 6 shows the loading error detecting mechanism 50.

[0053] The loading error detecting mechanism 50 includes the shutter 51 slidable in a direction perpendicular to the loading/unloading direction of the MD cartridge 150 along an upper front portion of the upper chassis 21, the drive plate 52 slidably supported on the reverse surface of the upper chassis 21, the switch unit 54 for detecting the presence of the MD cartridges 150 within the first to third stocker trays 16 to 18, and the right and left lock levers 32 and 33, as shown in Fig. 3(a), mounted on the first to third stocker trays 16 to 18.

[0054] The shutter 51 includes slide grooves 51a and 51b, the L-shaped slit 51c, the cam grooves 51d, and the shutter body 51e. The slide grooves 51a and 51b receive the pins 21a and 21b of the upper chassis 21 for guiding lateral movement of the shutter 51. Into the L-shaped slit 51c, the L-shaped protrusion 52e formed on the upper surface of the drive plate 52 is fitted through the groove 21e of the upper chassis 21. The cam grooves 51d receive the upper and lower pins 55a installed on upper and lower walls of the switch frame 55 of the switch unit 54. The shutter body 51e extends vertically and has the length corresponding to the total thickness of the first to third stocker trays 16 to 18.

[0055] The shutter 51 is, as will be described later in

detail, designed to detect errors in loading the MD cartridges 150 into the first to third stocker trays 16 to 18 and to cover the backs of the MD cartridges 150 partially when the MD cartridges 150 have been loaded into the first to third stocker trays 16 to 18 at a correct orientation for avoiding additional loading of new ones.

[0056] The drive plate 52 has the rack 52a, the cut-out portion 52b for avoiding the interference with the drive gear 64, as shown in Figs. 1, 2, and 7, the cam groove 53 into which the pin 12b of the base frame 12 is inserted, the guide protrusions 52c and 52d engaging the grooves 21c and 21d formed in the upper chassis 21, and the L-shaped protrusion 52e engaging the L-shaped slit 51c of the shutter 51. The rack 52a extends substantially perpendicular to the rack 12a of the base frame 12 and meshes with the drive gear 64 installed on the reverse surface of the upper chassis 21.

[0057] The cam groove 53 consists of five consecutive sections: the first straight section 53a, the first slant section 53b, the second straight section 53c extending in parallel to the first straight section 53a, the second slant section 53d, and the third straight section 53e extending substantially perpendicular to the first and second straight sections 53a and 53c.

[0058] The switch unit 54 consists of the frame 55 installed on the left side of the upper chassis 21 pivotably within a given angular range and three switches 58 attached to the frame 55 through the base plate 57. The switches 58 detect the presence of the MD cartridges 150 within the first to third stocker trays 16 to 18, respectively.

[0059] Fig. 7 shows the drive mechanism 60 designed to move the base frame 12 longitudinally of the chassis 11 of the stocker mechanism 10 and to move the shutter 51 of the loading error detecting mechanism 50 laterally.

[0060] The pivotal movement of the first to third stocker trays 16 to 18 relative to the base frame 12 and lateral movement of the shutter 51 of the loading error detecting mechanism 50 will be described later, and explanation thereof in detail will be omitted here.

[0061] The drive mechanism 60 includes a gear train consisting of the input gear 61a, the first and second intermediate gears 62 and 63, and the drive gear 64, the rack 12a installed, as already described, on the upper surface of the base frame 12, and the drive plate 52 that is also the part of the loading error detecting mechanism 50.

[0062] The input gear 61a is supported by the bracket 61, as shown in Fig. 2, and connected to an electric motor (not shown) to transfer motor torque to the drive gear 64 through the first and second intermediate gears 62 and 63.

[0063] The operation of the drive mechanism 60 will be discussed below with reference to Figs. 8 to 12.

[0064] Fig. 8 illustrates an neutral position of the drive mechanism 60 wherein the drive gear 64 is at rest, and the first to third stocker trays 16 to 18 of the stocker mechanism 10 are in the standby position. Specifically,

the first to third stocker trays 16 to 18 are oriented parallel to the base frame 12 with the front open ends facing forward.

[0065] The drive gear 64, as clearly shown in the drawing, meshes with the rack 52a of the drive plate 52. The pin 12b of the base frame 12 lies within the second straight section 53c of the cam groove 53 formed in the drive plate 52. The base frame 12 and the first to third stocker trays 16 to 18 are, therefore, placed in the rear-most position defined slightly ahead of the rear end of the upper chassis 21.

[0066] The shutter body 51e of the shutter 51 connected to the L-shaped protrusion 52e of the drive plate 52, as will be described later in detail, covers the front open ends of the first to third stocker trays 16 to 18 partially.

[0067] Fig. 9 illustrates a position of the drive mechanism 60 following the initial position shown in Fig. 8 wherein the drive mechanism 60 moves the first to third stocker trays 16 to 18 forward from the standby position through counterclockwise rotation of the drive gear 64.

[0068] When the drive gear 64 is rotated counterclockwise, it moves the rack 52a of the drive plate 52 to the left. Immediately before moved out of mesh with the track 52a, the drive gear 64 meshes with the rack 12a of the base plate 12 shown in Fig. 2. Subsequently, the drive gear 64 is moved out of mesh with the rack 12a and enters the cut-out portion 52b of the drive plate 52, thereby causing the pin 12b of the base frame 12 to move from the second straight section 53c toward the second slant section 53d of the cam groove 53 formed in the drive plate 52. When the pin 12b reaches the second slant section 53d of the cam groove 53, the base frame 12 starts to move forward through mesh of the drive gear 64 with the rack 12a of the base plate 12. Specifically, the second slant section 53d of the cam groove 53 switches the drive gear 64 from mesh with the rack 52a of the drive plate 52 to mesh with the rack 12a of the base plate 12. In other words, the second slant section 53d serves to switch the transmission of torque of the drive gear 64 from the drive plate 52 to the base plate 12 so that the lateral movement of the drive plate 52 is terminated, and longitudinal movement of the base plate 12 is initiated.

[0069] The shutter 51 is moved laterally through the lateral movement of the drive plate 52.

[0070] Fig. 10 illustrates a position of the drive mechanism 60 following the position shown in Fig. 9.

[0071] When the drive gear 64 is further rotated counterclockwise, it moves the base frame 12 forward through the rack 12a, thereby causing the pin 12b of the base frame 12 to proceed from the second slant section 53d to the third straight section 53e of the cam groove 53. The drive plate 52 is moved to and kept at the left-most position, so that the shutter 51e of the shutter 51 connected to the drive plate 52 opens the front ends of the first to third stocker trays 16 to 18 fully for allowing the loading of the MD cartridges 150.

[0072] Fig. 11 illustrates a position of the drive mechanism 60 following the position shown in Fig. 10 wherein the first and third stocker trays 16 to 18 reach the cartridge loading/unloading position and project from the chassis 11.

[0073] When the drive gear 64 continues to be rotated counterclockwise, it further moves the base frame 12 forward through the rack 12a from the position shown in Fig. 10. When the pin 12b of the base frame 12 reaches the front end of the third straight section 53e of the cam groove 53 formed in the drive plate 52, it will cause the base frame 12 to stop at the cartridge loading/unloading position where the MD cartridges 150 are to be loaded into or unloaded from the first to third stocker trays 16 to 18.

[0074] The shutter body 51e of the shutter 51 connected to the drive plate 52 is kept at the leftmost position and continues to open the front ends of the first to third stocker trays 16 to 18 fully.

[0075] Fig. 12 illustrates the loading position of the first to third stocker trays 16 to 18 which allows the MD cartridges 150 to be withdrawn or loaded from the first to third stocker trays 16 to 18 into the minidisk reproduction device 100.

[0076] After the MD cartridges 150 are loaded into the first to third stocker trays 16 to 18 at the cartridge loading/unloading position, the drive gear 64 of the drive mechanism 60 is reversed or rotated clockwise. The base frame 12 returns back to the standby position together with the first to third stocker trays 16 to 18 and moves backward of the upper chassis 21.

[0077] When the base frame 12 returns back to the standby position, the pin 12b of the base frame 12 engages the second straight section 53c of the cam groove 53, so that the drive gear 64 meshes with the rack 52a of the drive plate 52 again. The further clockwise rotation of the drive gear 64 causes the drive plate 52 to be moved to the right, so that the pin 12b of the base frame 12 travels along the first slant section 53b and the first straight section 53a of the cam groove 53, thereby causing the base frame 12 to be moved behind the standby position.

[0078] The shutter body 51e of the shutter 51 moves laterally through the lateral movement of the drive plate 52 and partially covers the rear ends of the MD cartridges 150 loaded into the first to third stocker trays 16 to 18.

[0079] The operation of the stocker mechanism 10 will be discussed below with reference to Figs. 13(a) to 17(b).

[0080] Figs. 13(a) and 13(b) both illustrate an initial position of the stocker mechanism 10 wherein the drive mechanism 60 is in the neutral position shown in Fig. 8, and the first to third stocker trays 16 to 18 are in the standby position within the chassis 11 and hold no MD cartridges 150. Fig. 13(a) illustrates the stocker mechanism 10 as viewed from the side of the right side chassis 22. Fig. 13(b) omits the right side chassis 22.

[0081] The pins 12d and 12e installed on the base frame 12 are movable forward along the grooves 22a and 22b formed in the right side chassis 22 by the distance A3 to slide the base frame 12 from the standby position toward the door unit 40 and also movable rearward by the distance B1 to slide the base frame 12 from the standby position toward the minidisk reproduction device 100. The distance A3 is longer than the distance B1.

[0082] The pin 25b installed on a rear portion of the right side plate 25 is inserted into the cam groove 22c of the base frame 12 through the elongated hole 15b of the cam plate 15 so as to be slidable along the cam groove 22c forward by the distance A3 and downward (i.e., toward the mount wall G of the chassis 11) by the distance C2 to swing the sub-frame 13 clockwise about the pin 25a installed on the front portion of the right side plate 25.

[0083] Fig. 13(b) shows the base frame 12, the sub-frame 13, the cam plate 15, and the first to third stocker trays 16 to 18 in the standby position.

[0084] The cam plate 15 is pivotably supported by the base frame 12 through the fit of the pivot 12i of the base frame 12 into the hole 15a of the cam plate 15. The cam plate 15 has, as described above, formed therein the laterally elongated hole 15b and the vertically elongated holes 15c and 15d. The pin 25b of the right side plate 25 of the sub-frame 13 passes through the laterally elongated hole 15b and enters the cam groove 22c of the base frame 12. The pins 31h installed on the rear portion of the second and third stocker trays 17 and 18 pass through the laterally elongated holes 25d and 25e of the right side plate 25 and enter the vertically elongated holes 15c and 15d of the cam plate 15. This allows the cam plate 15 to be rotated clockwise about the pivot 12i through movement of the pin 25b along the cam groove 22c of the base frame 12.

[0085] The first stocker tray 16 has the pins 31f fitted into the holes 25c of the right side plate 25 of the sub-frame 13 and is fixed horizontally on the upper inner wall of the right side plate 25.

[0086] The second and third stocker trays 17 and 18 have the front pins 31g inserted into the laterally elongated holes 25d and 25e of the right side plate 25 of the sub-frame 13 and the rear pins 31h, as described above, inserted into the laterally elongated holes 25d and 25e of the right side plate 25 and the vertically elongated holes 15c and 15d of the cam plate 15 so that they can move in parallel to the first stocker tray 16 and rotate about the pin 25a of the base frame 12 through the sub-frame 13.

[0087] In the standby position, the first to third stocker trays 16 to 18 are, as clearly shown in Fig. 13(b), lapped over one another with the front ends thereof being aligned with a line extending perpendicular to the mount wall G.

[0088] Figs. 14(a) and 14(b) both illustrate a position of the stocker mechanism 10 wherein the drive gear 64

of the drive mechanism 60 rotates, as shown in Fig. 9, to move the base frame 12 forward, as indicated by a white arrow in Fig. 14(a), from the standby position by the distance A1. Fig. 14(a) illustrates the stocker mechanism 10 as viewed from the side of the right side chassis 22. Fig. 14(b) omits the right side chassis 22.

[0089] In Fig. 14(a), the pins 12d and 12e installed on the base frame 12 move forward along the grooves 22a and 22b formed in the right side chassis 22 by the distance A1, so that the pin 25b lies at the front end of a horizontal section of the cam groove 22c. The sub-frame 13, the cam plate 15, and the first to third stocker trays 16 to 18 are, thus, remain unrotated. Specifically, the base frame 12, the sub-frame 13, the cam plate 15, and the first to third stocker trays 16 to 18 are, as shown in Fig. 14(b), oriented in parallel to the mount wall G.

[0090] Fig. 15(a) and 15(b) both illustrate a position of the stocker mechanism 10 wherein the base frame 12 is moved forward from the standby position by the distance A2. Fig. 15(a) illustrates the stocker mechanism 10 as viewed from the side of the right side chassis 22. Fig. 15(b) omits the right side chassis 22.

[0091] In Fig. 15(a), the pins 12d and 12e installed on the base frame 12 continue to move horizontally along the grooves 22a and 22b of the right side chassis 22, but the pin 25b on the right side plate 25 of the sub-frame 13 enters a slant section of the cam groove 22c and drops by the distance C1, thereby causing the sub-frame 13, the cam plate 15, and the first to third stocker trays 16 to 18 to rotate relative to the base frame 12.

[0092] The base frame 12, as clearly shown in Fig. 15(b), remains parallel to the mount wall G, while the sub-frame 13 swings clockwise through an angle α_1 about the pivot 25a on the base frame 12, and at the same time, the cam plate 15 swings through an angle β_1 about the pivot 12i on the base frame 12.

[0093] The swing of the sub-frame 13 causes the first to third stocker trays 16 to 18 to swing upward through the angle α_1 . The swing of the cam plate 15 thrusts through inner walls of the vertically elongated holes 15c and 15d the rear pins 31h mounted on the second and third stocker trays 17 and 18 forward along the laterally elongated holes 31h in the right side plate 25 of the sub-frame 13, thereby causing the front pins 31g on the second and third stocker trays 17 and 18 to slide along the elongated holes 25d and 25e in the right side plate 25 to thrust the second and third stocker trays 17 and 18 forward by different distances T1 and T2 which are determined as a function of intervals between the pivot 12i of the cam plate 15 and the pins 31h of the second and third stocker trays 17 and 18. The distance T1 is, thus, shorter than the distance T2, so that the third stocker tray 18 projects forwardest.

[0094] Figs. 16(a) and 16(b) both illustrate the front-most position of the stocker mechanism 10 wherein the base frame 12 is moved forward from the standby position by the distance A3 and reaches the cartridge loading/unloading position which allows the MD cartridges

150 to be loaded into or unloaded from the first to third stocker trays 16 to 18. Fig. 16(a) illustrates the stocker mechanism 10 as viewed from the side of the right side chassis 22. Fig. 16(b) omits the right side chassis 22.

[0095] In Fig. 16(a), the pins 12d and 12e installed on the base frame 12 move forward from the standby position by the distance A3 and reach the front ends of the grooves 22a and 22b of the right side chassis 22. The pin 25b on the right side plate 25 of the sub-frame 13 drops by the distance C2 and reaches the lowermost end of the cam groove 22c.

[0096] Specifically, the base frame 12, as clearly shown in Fig. 16(b), remains parallel to the mount wall G, while the sub-frame 13 swings clockwise through an angle α_2 about the pivot 25a on the base frame 12, and at the same time, the cam plate 15 swings through an angle β_2 about the pivot 12i on the base frame 12.

[0097] The swing of the sub-frame 13 through the angle α_2 causes the first to third stocker trays 16 to 18 to swing upward through the angle α_2 . The swing of the cam plate 15 through the angle β_2 advances the rear pins 31h mounted on the second and third stocker trays 17 and 18 along the laterally elongated holes 31h in the right side plate 25 of the sub-frame 13, thereby causing the front pins 31g on the second and third stocker trays 17 and 18 to slide along the elongated holes 25d and 25e in the right side plate 25 to thrust the second and third stocker trays 17 and 18 forward by different distances T3 and T4.

[0098] The angle α_2 through which the sub-frame 13 is rotated from the standby position is an inclination of the first to third stocker trays 16 to 18 to the mount wall G. The first stocker tray 16 is kept parallel to the upper plate 24 of the sub-frame 13, while the second and third stocker trays 17 and 18 are oriented upward at the angle α_2 to the mount wall G with the front ends projecting from that of the first stocker tray 16 by the distances T3 and T4.

[0099] When the MD cartridges 150 are loaded into the first to third stocker trays 16 to 18 correctly, the back surfaces MB of the MD cartridges 150 project in a step-wise fashion from the front ends of the first to third stocker trays 16 to 18 by the distance L0, respectively. This allows a user to grasp both sides of each of the MD cartridges 150 by fingers easily when replacing the MD cartridges 150 in the first to third stocker trays 16 to 18.

[0100] Figs. 17(a) and 17(b) both illustrate the rear-most position of the stocker mechanism 10 wherein the drive gear 64 of the drive mechanism 60 is reversed, as discussed with reference to Fig. 12, after the MD cartridges 150 are loaded into the first to third stocker trays 16 to 18 to move the base frame 12 backward across the standby position to the loading position which allows the MD cartridges 150 to be withdrawn from the first to third stocker trays 16 to 18 into the minidisk reproduction device 100. Fig. 17(a) illustrates the stocker mechanism 10 as viewed from the side of the right side chassis 22. Fig. 17(b) omits the right side chassis 22.

[0101] The pins 12d and 12e installed on the base frame 12 are, as shown in Fig. 17(a), moved backward horizontally, as indicated by a white arrow, along the grooves 22a and 22b formed in the right side chassis 22 by the distance B1 from the standby position shown in Fig. 13(a) and reach the rearmost ends of the grooves 22a and 22b. Similarly, the pin 25b is also moved backward horizontally along the horizontal section of the cam groove 22c by the distance B1 and reaches the rearmost end of the cam groove 22c. The sub-frame 13, the cam plate 15, and the first to third stocker trays 16 to 18, therefore, reach the loading position without being rotated.

[0102] The base frame 12, the sub-frame 13, the cam plate 15, and the first to third stocker trays 16 to 18 are, as shown in Fig. 17(b), oriented in parallel to the mount wall G.

[0103] The operation of the loading error detecting mechanism 50 will be discussed below with reference to Figs. 18(a) to 23(b).

[0104] Figs. 18(a) and 18(b) illustrate the first stocker tray 16 into which the MD cartridge 150 is loaded at a correct orientation.

[0105] In Fig. 18(a), M1 indicates a left groove formed in the MD cartridge 150, M2 indicates a right groove in the MD cartridge 150 for moving a shutter M3 thereof, and MF, MB, ML, and MR indicate the front, the back, the left side, and the right side of the MD cartridge 150, respectively.

[0106] Standard minidisk cartridges measure 71.4 mm by 68 mm and are marked Δ on upper surfaces indicating the loading direction, but users may not know the presence of the mark Δ and insert the minidisk cartridges into stocker trays at incorrect orientations. The loading error detecting mechanism 50 is provided for detecting such a loading error when the MD cartridge 150 is inserted into one of the first to third stocker trays 16 to 18 at the incorrect orientation.

[0107] When the MD cartridge 150 is loaded into, for example, the first stocker tray 16 at the correct orientation, the right and left sides MR and ML of the MD cartridge 150 are, as shown in Fig. 18(a), guided by the guide surfaces 31a and 31b in contact therewith. The MD cartridge 150 collides at the end of the left groove M1 with the hook 33b of the left lock lever 33 and stops. The back MB of the MD cartridge 150 projects from the front end of the first stocker tray 16 by the distance L0, allowing the user to hold the left and right sides ML and MR of the MD cartridge 150 by fingers. "S" indicates a reference line with which the back MB of the MD cartridge 150 coincides when loaded correctly.

[0108] Fig. 18(b) illustrates the MD cartridge 150 which has been loaded into the first stocker tray 16 at the correct orientation, but incompletely. Specifically, the clearance L1 is present between the end of the left groove M1 of the MD cartridge 150 and the hook 33b of the left lock lever 33, resulting in projection of the back MB of the MD cartridge 150 from the reference line by

the clearance L1.

[0109] Figs. 19(a) and 19(b) illustrate the MD cartridge 150 loaded into the first stocker tray 16 at incorrect orientations.

[0110] Fig. 19(a) illustrates the MD cartridge 150 which has been inverted laterally and vertically in error when loaded into the first stocker tray 16. The right groove M2 of the MD cartridge 150 does not agree in height with the hook 33b of the left lock lever 33, so that the MD cartridge 150 stops at the hook 33b, thereby resulting in projection of the back MB of the MD cartridge 150 from the reference line S by the distance L2.

[0111] Fig. 19(b) illustrates the MD cartridge 150 which has been turned 90° counterclockwise in error when loaded into the first stocker tray 16. Specifically, the front MF and the back MB of the MD cartridge 150 face the guide surfaces 31b and 31a of the first stocker tray 16, respectively. Since the depth D (= 58 mm) of the MD cartridge 150 is smaller than the interval between the guide surfaces 31a and 31b, clearances are developed between the right and left sides of the MD cartridge 150 and the guide surfaces 31a and 31b.

[0112] Therefore, when the MD cartridge 150 is, as shown in the drawing, loaded diagonally into the first stocker tray 16 with the left groove M2 being oriented laterally, it will cause the MD cartridge 150 to collide at the left groove M2 with the hook 33b of the left lock lever 33 so that it stops at the hook 33b, thus resulting in projection of the left side ML from the reference line S by the distance L3. Even when the MD cartridge 150 is loaded into the first stocker tray 16 in parallel, the left side ML projects from the reference line S.

[0113] Fig. 20 illustrates the state of the loading error detecting mechanism 50 when the MD cartridge 150 is being loaded at the correct orientation into, for example, the first stocker tray 16 which is in the cartridge loading/unloading position.

[0114] When loaded into the first stocker tray 16, the MD cartridge 150 is guided at the right and left side surfaces MR and ML by the guide surfaces 31a and 31b of the first stocker tray 16. The shutter body 51e of the shutter 51 lies on the left side of the first stocker tray 16 at an interval δ away from the left side surface ML of the MD cartridge 150. After loaded into the first stocker tray 16 completely, the MD cartridge 150 is moved to the standby position.

[0115] Figs. 21(a) and 21(b) illustrate the state of the loading error detecting mechanism 50 when the MD cartridges 150 reach the standby position after loaded into the first to third stocker trays 16 to 18 correctly.

[0116] When the MD cartridges 150 are loaded into the first to third stocker trays 16 to 18 completely, the back MB of each MD cartridge 150, as shown in Fig. 18(a), projects from the front end of corresponding one of the first to third stocker trays 16 to 18 by the distance L0, but it is located behind the shutter 51. Specifically, the distance L0 is so determined that the back MB of each MD cartridge 150 does not interfere with the shut-

ter 51. Thus, when the shutter 51 is moved right, as viewed in the drawings, it covers the back MB of each MD cartridge 150 partially with a given clearance, thereby avoiding additional loading of MD cartridges into the first to third stocker trays 16 to 18.

[0117] Fig. 22 illustrates the state of the loading error detecting mechanism 50 when the MD cartridge 150 is turned 90° counterclockwise in error and loaded into the first stocker tray 16 with the front MF and the back MB of the MD cartridge 150 facing the guide surfaces 31b and 31a of the first stocker tray 16, respectively.

[0118] For example, when the back MB of the MD cartridge 150 is brought close to the right guide surface 31a of the first stocker tray 16, the shutter body 51e of the shutter 51 is located at the leftmost position at an interval $\delta 2$ away from the front MF of the MD cartridge.

[0119] Figs. 23(a) and 23(b) illustrate the state of the loading error detecting mechanism 50 when the MD cartridges 150 reach the standby position after one of the MD cartridge 150 is loaded into the first stocker tray 16 at the incorrect orientation shown in Fig. 22.

[0120] The left side ML of the MD cartridge 150 loaded into the first stocker tray 16, as shown in Fig. 19(b), projects from the reference line S. When the shutter 51 is, thus, moved right, it will cause the shutter body 51e to collide with the front MF of the MD cartridge 150 in the first stocker tray 16 so that it stops. This results in an increase in load of the electric motor of the drive mechanism 60, which may be detected by monitoring an overcurrent flowing through the electric motor. Therefore, when such an overcurrent is detected, it may be determined that at least one of the MD cartridges 150 has been loaded into corresponding one of the first to third stocker trays 16 to 18 at an incorrect orientation. The removal of the MD cartridge loaded at the incorrect orientation is achieved easily by reversing the shutter 51 through a control circuit (not shown).

[0121] While the present invention has been disclosed in terms of the preferred embodiment in order to facilitate a better understanding thereof, it should be appreciated that the invention can be embodied in various ways without departing from the principle of the invention. Therefore, the invention should be understood to include all possible embodiments and modification to the shown embodiments which can be embodied without departing from the principle of the invention as set forth in the appended claims.

[0122] A stocker apparatus for storage mediums such as minidisk cartridges is provided which includes a stocker tray moving mechanism designed to move stocker trays between a neutral and a storage medium loading/unloading position together. In the neutral position, the stocker tray moving mechanism lays the stocker trays to overlap each other with storage medium loading/unloading openings being aligned vertically. In the storage medium loading/unloading position, the stocker tray moving mechanism shifts the stocker trays laterally by different distances so as to orient the stor-

age medium loading/unloading openings diagonally upward for facilitating ease of manual loading and unloading of each storage medium into and from corresponding one of the stocker trays.

Claims

1. A stocker apparatus for storage mediums comprising:

a plurality of stocker trays for stocking therein storage mediums, respectively, each of said stocker tray having a storage medium loading/unloading opening; and

a stocker tray moving mechanism designed to move said stocker trays between a first and a second position together, in the first position, the stocker tray moving mechanism laying said stocker trays so as to overlap each other with the storage medium loading/unloading openings being aligned substantially perpendicular to a reference plane, in the second position, the stocker tray moving mechanism shifting the stocker trays laterally by different distances so as to orient the storage medium loading/unloading openings upward in alignment with a diagonal line extending at a given angle to the reference plane for loading and unloading the storage mediums into and from said stocker trays.

2. A stocker apparatus as set forth in claim 1, wherein said stocker tray moving mechanism includes a chassis, a base frame, a sub-frame, a cam groove, and a cam plate, the base frame being installed on the chassis so as to be movable substantially parallel to the reference plane, the sub-frame being mounted pivotably on the base frame and retaining said stocker trays to overlap each other vertically, the cam groove being formed in the chassis along which a cam follower connecting with the sub-frame moves to swing the sub-frame relative to the base frame according to movement of the base frame substantially parallel to the reference plane, the cam plate being supported pivotably by a pivot installed on the base frame and thrusting said stocker trays laterally from the sub-frame by the different distances which are determined as a function of intervals between the pivot on the base frame and said stocker trays.
3. A stocker apparatus as set forth in claim 2, further comprising a door which opens and closes a storage medium loading/unloading openings of the chassis selectively according to the movement of the base frame.
4. A stocker apparatus for storage mediums comprising:

ing:

a plurality of stockers laid to overlap each other in a direction substantially perpendicular to a loading/unloading direction in which cartridges holding therein storage mediums are loaded into and unloaded from said stockers, each of said stockers being designed to receive the cartridge inside a reference line when the cartridge is loaded at a correct orientation and to project an end portion of the cartridge from the reference line when the cartridge is loaded at an incorrect orientation; and
a shutter provided to be movable between a first and a second position in a direction substantially perpendicular to the loading/unloading direction of the cartridges, in the first position, said shutter lying at a given interval away from the cartridges without interfering with loading and unloading of the cartridges into and from said stockers, in the second position, said shutter covering the end portions of the cartridges at least partially when all the cartridges are loaded into said stockers at the correct orientation and colliding with the end portion of at least one of the cartridges projecting from the reference line when the at least one of the cartridge is loaded into corresponding one of said stockers at the incorrect orientation.

5. A stocker apparatus for storage medium comprising:

a stocker mechanism having a stocker frame retaining a plurality of stocker trays for stocking therein cartridges which hold storage mediums, said stocker mechanism moving the stocker trays between a first and a second position together, in the first position, the stocker trays being laid to overlap each other with storage medium loading/unloading openings being aligned substantially perpendicular to a reference plane, in the second position, the stocker trays being shifted laterally relative to the stocker frame for facilitating ease of loading and unloading of each of the cartridges into and from corresponding one of the stocker trays, each of the stocker trays being designed to receive the cartridge inside a reference line when the cartridge is loaded at a correct orientation and to project an end portion of the cartridge from the reference line when the cartridge is loaded at an incorrect orientation; and
a shutter provided to be movable between a first and a second shutter position in a direction substantially perpendicular to the load-

ing/unloading direction of the cartridges, in the first shutter position, said shutter lying at a given interval away from the cartridges without interfering with loading and unloading of the cartridges into and from said stocker trays, in the second shutter position, said shutter covering the end portions of the cartridges at least partially when all the cartridges are loaded into said stocker trays at the correct orientation and colliding with the end portion of at least one of the cartridges projecting from the reference line when the at least cartridge is loaded into corresponding one of said stocker trays at the incorrect orientation.

6. A stocker apparatus as set forth in claim 5, wherein said stocker mechanism includes a cam mechanism which moves the stocker trays and said shutter.
7. A stocker apparatus as set forth in claim 5, wherein said shutter covers the end surfaces of the cartridges at least partially when all the cartridges are loaded into said stocker trays at the correct orientation for avoiding additional loading of cartridges.




FIG. 1




FIG. 2




FIG. 3(a)

FIG. 3(b)




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13(a)




FIG. 13(b)




FIG. 14(a)






FIG. 14(b)






FIG. 16(a)




FIG. 16(b)




FIG. 17(a)




FIG. 17(b)




FIG. 18(b)

FIG. 18(a)




FIG. 19(b)

FIG. 19(a)




FIG. 20




FIG. 21(a)




FIG. 21(b)






FIG. 22





Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 0 905 686 A3**

(12) **EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:
07.07.1999 Bulletin 1999/27

(51) Int. Cl.⁶: **G11B 15/68, G11B 17/22**

(43) Date of publication A2:
31.03.1999 Bulletin 1999/13

(21) Application number: **98118059.9**

(22) Date of filing: **23.09.1998**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE**
Designated Extension States:
AL LT LV MK RO SI

(30) Priority: **24.09.1997 JP 25904697**

(71) Applicant:
**Victor Company of Japan, Ltd.
Yokohama 221-0022 (JP)**


(72) Inventors:
• **Yamanaka, Akira**
Yokohama (JP)
• **Shibuya, Naoki**
Takasaki-chi, Gunma-ken (JP)

• **Yomogida, Yasukazu**
Sagamihara-shi, Kanagawa-ken (JP)
• **Nishikawa, Kouichiro**
Sagamihara-shi, Kanagawa-ken (JP)
• **Adachi, Kengo**
Sagamihara-shi, Kanagawa-ken (JP)
• **Shintani, Isao**
Maebashi-shi, Gumma-ken (JP)

(74) Representative:
Pellmann, Hans-Bernd, Dipl.-Ing. et al
Patentanwaltsbüro
Tiedtke-Bühling-Kinne & Partner
Bavariaring 4
80336 München (DE)

(54) **Improved structure of stocker apparatus for storage medium**

(57) A stocker apparatus for storage mediums such as minidisk cartridges is provided which includes a stocker tray moving mechanism designed to move stocker trays between a neutral and a storage medium loading/unloading position together. In the neutral position, the stocker tray moving mechanism lays the stocker trays (16, 17, 18) to overlap each other with storage medium loading/unloading openings being aligned vertically. In the storage medium loading/unloading position, the stocker tray moving mechanism shifts the stocker trays laterally by different distances so as to orient the storage medium loading/unloading openings diagonally upward for facilitating ease of manual loading and unloading of each storage medium into and from corresponding one of the stocker trays.





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 98 11 8059

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X	DE 29 29 172 A (POEHLER MICROFILM APP MAP) 5 February 1981 * page 8, paragraph 3 - page 9, paragraph 1; figures 1-3 *	1	G11B15/68 G11B17/22
A	EP 0 215 767 A (STAAR SA) 25 March 1987 * abstract; figure 3 *	1-3,5-7	
A	EP 0 063 894 A (AMLYN CORP) 3 November 1982 * figures 5,7 *	1,5	
			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
			G11B
<p>The present search report has been drawn up for all claims</p>			
Place of search THE HAGUE		Date of completion of the search 4 December 1998	Examiner SOZZI, R
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EP 0 905 686 A3 (P04C01)



European Patent
Office

Application Number

EP 98 11 8059

CLAIMS INCURRING FEES

The present European patent application comprised at the time of filing more than ten claims.

- ☐ Only part of the claims have been paid within the prescribed time limit. The present European search report has been drawn up for the first ten claims and for those claims for which claims fees have been paid, namely claim(s):
- ☐ No claims fees have been paid within the prescribed time limit. The present European search report has been drawn up for the first ten claims.

LACK OF UNITY OF INVENTION

The Search Division considers that the present European patent application does not comply with the requirements of unity of invention and relates to several inventions or groups of inventions, namely:

see sheet B

- ☐ All further search fees have been paid within the fixed time limit. The present European search report has been drawn up for all claims.
- ☐ Only part of the further search fees have been paid within the fixed time limit. The present European search report has been drawn up for those parts of the European patent application which relate to the inventions in respect of which search fees have been paid, namely claims:
- ☒ None of the further search fees have been paid within the fixed time limit. The present European search report has been drawn up for those parts of the European patent application which relate to the invention first mentioned in the claims, namely claims:

1 - 3 , 5 - 7



European Patent
Office

**LACK OF UNITY OF INVENTION
SHEET B**

Application Number
EP 98 11 8059

The Search Division considers that the present European patent application does not comply with the requirements of unity of invention and relates to several inventions or groups of inventions, namely:

1. Claims: 1-3,5-7

A stocker apparatus comprising:

- a plurality of stocker trays,
- a stocker tray moving mechanism.

2. Claim : 4

A stocker apparatus comprising:

- a plurality of stockers,
- a shutter arranged in a way to be movable in a direction substantially perpendicular to the loading/unloading direction of the cartridges.

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 98 11 8059

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

04-12-1998

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE 2929172 A	05-02-1981	NONE	
EP 0215767 A	25-03-1987	BE 903223 A	31-12-1985
		BE 904766 A	01-09-1986
		AT 61146 T	15-03-1986
		CA 1276566 A	20-11-1990
		JP 2020372 C	19-02-1996
		JP 7058577 B	21-06-1995
		JP 62117164 A	28-05-1987
		US 4701899 A	20-10-1987
EP 0063894 A	03-11-1982	US 4453188 A	05-06-1984
		AU 8239382 A	14-10-1982
		JP 57179968 A	05-11-1982

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82